

DC – DC CONVERTERS MODEL DY 24500 (2U) Slim line (48V/10 A)



ELECTRICAL SPECIFICATIONS

INPUT SPECIFICATIONS

Nominal Voltage	24 VDC
Voltage Range	20 - 30 VDC
Switching Frequency	100KHz
Efficiency	≥ 85 %
Input Current	30A Max
Input Over Voltage Protection	32V Max
Dielectric Strength	1.5KV AC (I/P to O/P & Case)

OUTPUT SPECIFICATIONS

Output Voltage	48V DC
Output Current	10A
Current Limit	11A (Max)
Power	500 Watts
Output Voltage Trim	Adjustable from 43.2 – 52.8V
Ripple	< 1% of output p-p
Net Regulation	± 0.1V

SPECIAL FEATURES

- ❖ 2U Height
- ❖ 19" Rack Mountable / Table top
- ❖ Over Voltage Protection: 102% Max of Output
- ❖ Over Load Protection : Fold back type
- ❖ Short Circuit Protection: Provided with Auto Recovery

MECHANICAL

Dimensions	483(19") (W) x 330 (D) x 2U (H) mm
Weight	6Kg
Input & Output Connector	12 pin Mate-N-Lok plug
Enclosure	IP20, CRC Sheet Powder Coated 19" Rack Mounting

ENVIRONMENT & SAFETY

Operating Temperature	0 °C to 50°C
Storage Temperature	-10°C to 70°C
Cooling	Convection
Operating Humidity	≤ 95 % RH
Safety	Designed to meet IEC 60950
EMI / EMC	Designed to meet CISPR22 Class A/ IEC 61000- 4

[Specification No - DCDC / DY 24500 – \(Rev. 0\)](#)

*Specifications may or can be altered without notice as per company's continuous improvement Program.