

## DC – DC CONVERTERS MODEL DY 248500A (48V/10A X 2)



MODEL 248500A is a Modular Power System, which uses 2 nos. Hot-Pluggable DY 48500A DC-DC Converter Modules of 500 Watts.

### ELECTRICAL SPECIFICATIONS

#### INPUT SPECIFICATIONS

Nominal Voltage	50 VDC
Voltage Range	40 - 60 VDC
Switching Frequency	100KHz
Efficiency	90 % TYPICAL
Input Current	30A Max
Input Over Voltage Protection	62V Max
Dielectric Strength	1.5KV AC (I/P to O/P & Case)

#### OUTPUT SPECIFICATIONS

Output Voltage	48V DC
Output Current	20A
Current Limit	22A (Max)
Power	1000 Watts
Output Voltage Trim	46 – 50VDC(Min)
Ripple	< 1% of output p-p
Net Regulation	± 5V

#### SPECIAL FEATURES

- ❖ Transducer for Remote Monitoring 4 – 20mA
- ❖ Potential free contact for Output fail
- ❖ Active current sharing for Parallel Operation

#### MONITORING DISPLAY

Digital Panel Meter Provided for  
OUTPUT : VOLTS & AMPS

#### MECHANICAL

Dimensions	483 (W) x 410 (D) x 280 (H) mm
Weight	22Kg
Input & Output	MCB Terminals
Enclosure	IP20, CRC Sheet Powder Coated 19" Rack Mounting

#### ENVIRONMENT & SAFETY

Operating Temp	0 °C to +50°C
Storage Temperature	-10°C to 70°C
Cooling	Convection
Operating Humidity	≤ 95% RH
Safety	Designed to meet IEC 60950
EMI/ EMC	Designed to meet CISPR22 Class A/ IEC 61000- 4

[Specification No - DCDC / DY 248500A – \(Rev. 0\)](#)

\* Enhancement to the above specifications & Customizing can be considered on request.

\* Specifications may or can be altered without notice as per company's continuous improvement Program.